

# Product Specifications

## FlashTrak™ TMX Data Logger

<b>Measurement Range</b>	-40°F to 158°F (-40°C to 70°C)
<b>Operating Range</b>	-40°F to 158°F (-40°C to 70°C)
<b>Radio Frequency Range</b>	up to 250M (820 ft) line of sight
<b>RF Bands</b>	915 MHz 868 MHz ISM band (available by special order)
<b>Programmable Measurement Interval</b>	5 minute default
<b>Resolution</b>	0.2°F (0.1°C)
<b>Accuracy</b>	±1.0°F from -4°F to 113°F (±0.5°C from -20°C to 45°C) ±4°F above 113° (±2°C above 45°C) ±2°F below -4° (±1°C below -20°C)
<b>Data Capacity</b>	2,730 data points
<b>Power Source</b>	2 AA Lithium Pack
<b>Battery Life</b>	Up to 1.5 yrs 5 yr shelf life
<b>Antenna</b>	External omnidirectional fixed antenna
<b>Weight</b>	14 oz (397 g)
<b>Dimensions</b>	148mm x 171mm x 34mm (10.5 in x 7.75 in x 2.75 in)
<b>LED Indicator</b>	Red – Sending data
<b>Button</b>	Single user button
<b>Waterproof Rating</b>	IP65
<b>Certification</b>	FCC, CE, NIST, RoHS, WEEE



### Model 22080

- Wireless data logger for FlashTrak Telematics System
- Probeless product temperature monitoring with Product Emulation Tool through ColdTrak.com
- Alert notification with two high (high & extreme high) and two low (low & extreme low)
- Secure mounting bracket

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS 22080 17H2

