

# Product Specifications

## FlashTrak Telematics Data Logger

|                              |  |
|------------------------------|--|
| <b>Measurement Range</b>     | -22°F to 140°F (-30°C to 40°C)                           |
| <b>Radio Frequency Range</b> | up to 250M (820 ft) line of sight                        |
| <b>RF Bands</b>              | 915 MHz<br>868 MHz ISM band (available by special order) |
| <b>Sample Interval</b>       | Factory programmable. Default setting: 5 min.            |
| <b>Resolution</b>            | 0.2°F (0.1°C)  |
| <b>Accuracy</b>              | ±0.3°C for 12 months after calibration                   |
| <b>Data Capacity</b>         | 2,730 data points  |
| <b>Power Source</b>          | MnO <sub>2</sub> Battery                                 |
| <b>Battery Backup</b>        | AAA Lithium  |
| <b>Battery Life</b>          | up to 2.5 yrs<br>5 yr shelf life                         |
| <b>Weight</b>                | 2.65 oz  |
| <b>Dimensions</b>            | 65mm x 50mm x 36mm<br>(2.56 in x 1.96 in x 1.41 in)      |
| <b>LED Indicator</b>         | Green – Sending data                                     |
| <b>Waterproof Rating</b>     | IP67   |
| <b>Certification</b>         | FCC, CE, RoHS, WEEE, NIST                                |



### Model 22081

- Wireless data logger for FlashTrak Telematics System
- Non-invasive internal product monitoring with Product Emulation
- Data visible 24/7 on ColdTrak Data Central cloud service
- Alert notifications with four set points: high and extreme high, low and extreme low
- Security wall mount bracket

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS0161 18J1

