

# Product Specifications

## FlashTrak Telematics Data Logger with External Probe

<b>Probe Measurement Range</b>	-40°F to 104°F (-40°C to 40°C)
<b>Operating Range</b>	-22°F to 140°F (-30°C to 40°C)
<b>Radio Frequency Range</b>	up to 250M (820 ft) line of sight
<b>RF Bands</b>	915 MHz 868 MHz ISM band (available by special order)
<b>Sample Interval</b>	Factory programmable. Default setting: 5 min.
<b>Resolution</b>	0.2°F (0.1°C)
<b>Accuracy</b>	±1.0°F (±0.5°C) from -40°F to 86°F (-40°C to 30°C) ±2.0°F (±1.0°C) above 86°F (30°C)
<b>Data Capacity</b>	2,730 data points
<b>Power Source</b>	Lithium Battery
<b>Battery Life</b>	up to 2.5 yrs 5 yr shelf life
<b>Weight</b>	2.65 oz
<b>Logger Dimensions</b>	59mm x 106mm x 17mm (2.32 in x 4.17 in x 0.66 in)
<b>Probe/Cable Dimensions</b>	101mm L x 3.5mm D (3.98 in L x 0.14 in D) with 2.899m (9.5 ft) Teflon cable
<b>LED Indicator</b>	Green – Sending data
<b>Waterproof Rating</b>	IP67
<b>Certification</b>	FCC, CE, RoHS, WEEE, NIST



### Model 22105

- Wireless data logger for FlashTrak Telematics System
- Sharp tip probe for monitoring internal product temperature
- Data visible 24/7 on ColdTrak Data Central cloud service
- Alert notifications with four set points: high and extreme high, low and extreme low

Accessory: Data logger cradle with security bracket (model 22111)

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS 22105 17H1

