

Product Specifications

FlashLink® Reusable Real-Time Mini Data Logger

Temperature Range	-22°F to 140°F (-30°C to 60°C)
Temperature Accuracy	±1°F (0.5°C) from 14°F to 50°F (-10°C to 10°C) ±2°F (1°C) from 50°F to 140°F (10°C to 60°C)
Temperature Resolution	0.1
Humidity Measurement Range	20% to 90% RH
Humidity Accuracy	±3% at 50% RH at 77°F (25°C)
Humidity resolution	0.1% RH
GSM Network	2G Quad band GSM 850/900/1800/1900 MHz
Log Interval	5 minutes
Upload Interval	5 minutes
Log Duration	Perpetual logging with USB-C power cable (provided) and 10 day minimum on full battery charge, without external power supply
Battery	Lithium-ion battery, rechargeable
Weight	6.21 oz (176 grams)
Logger Dimensions	3.74in x 3.74in x 1.1in (95mm x 95mm x 28mm)
Certification	FCC, CE Mark, Temperature & Humidity Sensor NIST traceable



Model 22302

22302-01	Includes 1-yr FlashTrak RU Cloud Service
22302-02	Includes 2-yr FlashTrak RU Cloud Service

- Rechargeable and programmable
- Monitors location, temperature, humidity
- Data transmitted via GSM cellular networks
- No need to open vehicle doors to access information
- 24/7 cloud service to view and analyze data remotely
- Make immediate cold chain management decisions
- Customize settings for high/low alarm limits
- Data stored in the cloud for traceability, audits, HACCP, and FSMA compliance

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system

SS 22302-01-X 2111

